

WELL LOG AND REPORT TO THE STATE  
ENGINEER OF NEVADA

Log No. 52963  
 Rec. 19  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Do not file in

Owner Conice Bals  
AD Bals Driller O. McQuillan

Address \_\_\_\_\_ Address Rt #1 - Box 92 Lic. No. 115

Location of well: NE 1/4 1/4 Sec. 24, T. 21 N/S, R. 6 E, in Las Vegas - Clark County  
 or M.B.M.

Water will be used for Domestic Total depth of well 150 ft

Size of drilled hole 50 ft - 10" 100 ft - 6" Weight of casing per linear foot \_\_\_\_\_

Thickness of casing 10 gauge Temp. of water \_\_\_\_\_

Diameter and length of casing 6" O.D. 150 ft  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface \_\_\_\_\_

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well 10-14-55 Date of completion of well 10-20-55

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	6	6	White Clay & Sand	Chief aquifer (water-bearing formation) from <u>145</u> to <u>147</u> ft.
6	32	26	Light Brown Clay	
32	34	2	Sand & Gravel - 1st W.	Other aquifers _____
34	103	69	Dark Brown Clay	<u>106-110</u>
103	106	3	Sandstone	_____
106	110	4	Soft Brown Mud & Water	_____
110	141	31	Dark Brown Clay	_____
141	145	4	Sandstone	First water at <u>92</u> feet.
145	147	2	Gravel - Water	Casing perforated
147	150	3	Limestone	from <u>105</u> to <u>150</u> ft.
				Size of perforations <u>1/8" x 8</u>

