WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 52964
Rec. [redacted] 9
Well No.
Permit No.
Do not fill in

Owner: Benson
Driller: Rodgers & Smith
Address:
Address:
Lic. No. 31

Location of well: SW NW ¼ ¼ Sec. 34, T. 21 N/S, R. 61 E, in Clark County
or E½ SE¼ SW¼ NW¼

Water will be used for: Domestic
Total depth of well: 100

Size of drilled hole: 10 in
Weight of casing per linear foot: 16

Thickness of casing: 10 Gage
Temp. of water:

Diameter and length of casing: 8 in OD 88
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 32

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: July 5 [illegible]
Date of completion of well: July 12 [illegible]

Type of well rig: Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	Silt sand and gravel
6	26	20	White Clay Solid
26	40	14	Pink Clay Soft
40	42	2	Gravel water
42	65	23	Brown Clay
65	70	5	Decomposed Lime light
70	96	26	Pink Sandy Clay
96	98	2	gravel water
98	105	7	Pink Sandy Clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 96 to 98 ft.

Other aquifers 40, 65

First water at 40 feet.

Casing perforated
from 65 to 85 ft.

Size of perforations
1/4 x 4

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8.OD	0	88	88 ft 8 in OD	Cemented To 60 ft 1 yd. readymix

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed.....
Well Driller

By S.B. Rodgers

License No. 31

Dated July 30, 1952

(Not to be filled in by Driller)