

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 63578  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Floyd Draper Driller S.R. McKinney & Son  
 Address General Delivery, Indian Springs, Nevada Address 1042 South Main, L.V. Lic. No. 45  
 Location of well: NE 1/4 NE 1/4 Sec. 11, T. 20 N/S, R. 60 E, in. Clark County \_\_\_\_\_  
 or \_\_\_\_\_  
 Water will be used for Domestic Total depth of well 125'  
 Size of drilled hole 12" to 50', 10" to 125' Weight of casing per linear foot 10 Guage  
 Thickness of casing 10 Guage Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" I.D. to 125'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 55'  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well May 11, 1955 Date of completion of well May 12, 1955  
 Type of well rig Bucyrus Erie 24-L, Spudder

## LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	10	10	Top Soil
10	20	10	Sandy Clay
20	30	10	Caliche
30	40	10	Sandy Clay
40	55	15	Caliche
50	70	20	Sandy Clay
70	75	5	Sand & little water
75	90	15	Sandy clay
90	110	20	Sandy Brown Clay
110	111	1	Decomposed Lime water
111	115	4	Brown Clay
115	120	5	Sandy water
120	125	5	Brown Clay

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 115 to 120 ft.  
 Other aquifers 110' to 111'  
70' to 75'

---

First water at 70' feet.

---

Casing perforated  
 from 75 to 125 ft.

---

Size of perforations  
3/16" x 10"

