


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 53691
 Rec. _____ 19____
 Well No. _____
 Permit No. _____
 Do not fill in

Owner Steve Evans Staskowitz Driller Effinger Bros.
 Address 636 Bell Street Las Vegas Address 212 Anderson Lane Lic. No. _____
 Location of well: 1/4 NW 1/4 Sec. 12, T20 N/S, R60 E, in Clark County
 or Lot 1, Block 8 Tonopah Terrace Edward Avenue
 Water will be used for Domestic Total depth of well 125 feet
 Size of drilled hole 10 inch Weight of casing per linear foot 12.06 lbs.
 Thickness of casing 10 Gauge Temp. of water _____
 Diameter and length of casing 8 5/8" OD 80 feet
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 57'8" from top of casing
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well Sept. 15, 1954 Date of completion of well Sept. 17, 1954
 Type of well rig "71 Speed Star"

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	1	1	Sand
1	28	27	Limestone
28	33	5	Yellow Sticky Clay
33	39	6	Limestone
39	43	4	Yellow Sandy Clay
43	51	8	Limestone
51	56	5	White Clay
56	63	7	Limestone
63	64	1	Sand (Water)
64	79	15	Limestone
79	105	26	Sandy Clay & Gravel (Water)
105	125	20	Limestone

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 79 to 105 ft.

Other aquifers 63-64

First water at 63 feet.

Casing perforated

from 60 to 80 ft.

Size of perforations

1/8" X 12"



