

LVD

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 53853

Res. No. _____ 19____

Well No. _____

Permit No. _____

Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner XXX Jim Edwards Driller S. E. McKinney & Son, Inc.

Address 1881 Leonard Lane Las Vegas Address _____ Lic. No. 45

Location of well: NW 1/4 SE 1/4 Sec. 24, T20 N/S, R. 60 E, in Clark County _____
or _____

Water will be used for Domestic Total depth of well 250 ft.

Size of drilled hole 12" to 50 ft., 10" to 250 Weight of casing per linear foot 3/16"

Thickness of casing 3/16" Temp. of water _____

Diameter and length of casing 8 5/8 inch O.D. from 0 to 250 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 133 ft.

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well 4-8-66 Date of completion of well 4-14-66

Type of well rig Eucyrus Erie 24 L Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	top soil
3	9	6	gravel
9	16	7	white clay
16	20	4	caliche
20	40	20	white graveley clay
40	48	8	brown clay
48	50	2	cemented gravel
50	54	4	brown clay
54	61	7	gravel and clay
61	136	75	brown clay
136	140	4	cemented gravel
140	143	3	sandy clay
143	155	12	cemented gravel water
155	181	26	cemented gravel
181	195	14	cemented gravel water
195	225	30	cemented gravel
225	250	25	cemented gravel water

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 225 to 250 ft.

Other aquifers 181 to 195

143 to 155

First water at 143 feet.

Casing perforated

from 110 to 250 ft.

Size of perforations

3/16" X 10"

