

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 5386
 Rec. 19
 Well No.
 Permit No.
Do not fill in

Owner ROY R. DEXTER Driller HOWARD & SON

Address c/o Car Foreman UP. Railroad, LV Nev. Address 2600 Webb, N. LV Nev. Lic. No. 134

Location of well: N¹/₂ NE ¹/₄ SW ¹/₄ Sec. 33, T. 22 N/S, R. 61 E, in Clark County

Water will be used for domestic Total depth of well 160 ft.

Size of drilled hole 8" (12" to depth of 50 ft) Weight of casing per linear foot 25#

Thickness of casing 1/4" Temp. of water

Diameter and length of casing 8" - 161 ft.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 118 ft.

If flowing well describe control works

Date of commencement of well May 26, 1955 Date of completion of well 6/2/55

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	32	32	Gravel
32	126	94	Clay & Rock Conglomerate
126	135	9	Sand and fine Gravel
135	150	15	Sandstone
150	160	10	Sand & Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 150 to 160 ft.

Other aquifers

First water at 126 feet.

Casing perforated

from 125 to 160 ft.

Size of perforations

1/4" x 4"

