WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 54037
Rec. 19
Well No. .....
Permit No. .....
Do not fill in

Owner: Eldon Bona Driller: Patrick H. Thompson

Address: 811 Upland, Las Vegas, Nev. Address: 217 S. 26th St. L.V.N. Lic. No. 192

Location of well: SE ¼ SW ¼ Sec. 36, T 20 N/S, R 60 E, in Clark County

or .....

Water will be used for: Domestic Total depth of well: 300'

Size of drilled hole: 12" to 150' - 10" from 150 to 300' Weight of casing per linear foot: 13#

Thickness of casing: 10 guage Temp. of water: cool

Diameter and length of casing: 8-5/8" dia. -- 301' length
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface: 168'

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well: Aug. 21, 1962 Date of completion of well: Sept. 5, 1962

Type of well rig: Cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	28	28	caliche
28	43	15	red clay and sand
43	49	6	caliche
49	142	93	red sandy clay
142	300	158	cemented gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 168 to 300 ft.

Other aquifers .....

First water at 168 feet.

Casing perforated

from 170 to 300 ft.

Size of perforations

3/16" x 12" - 4 rows

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8-5/8	+	300	301	Cemented to 55'

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bail test 30 G.P.M. from 168'

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Patrick N. Thompson
Well Driller

By .....

License No. 192

Dated Oct. 16, 1, 1962

(Not to be filled in by Driller)