


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA



Log No. 2021 54022
 Rec. 7-22 1955
 Well No. _____
 Permit No. 15470
Do not fill in

Owner Mrs. Lambert Van Der Meer Driller S.R. McKinney & Son

Address 10102 North Main, Las Vegas, Nev. Address 1042 South Main, L.V. Lic. No. 45

Location of well: ^{SW} ~~NE~~ NE $\frac{1}{4}$ NE $\frac{1}{4}$ Sec. 23, T. 20 N/S, R. 61 E, in Clark County

Water will be used for D & I Total depth of well 560'

Size of drilled hole 6" to 560' Weight of casing per linear foot ~~16.5~~ 16'

Thickness of casing ~~12" 4" Wall~~ Temp. of water _____

Diameter and length of casing 6" I.D. from 139' to 560'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 42'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well 29 June 1955 Date of completion of well 13 July 1955

Type of well rig Bucyrus Erie 24L, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
200	225	25	Clay
225	323	7	Sandy clay
222	250	18	Clay
250	253	3	Gravel
253	260	7	Clay
260	283	23	Sandy clay
283	365	82	Clay
365	395	30	Clay
395	412	17	Sandy clay
412	480	68	Clay
480	515	35	Sandy clay
515	520	5	Sand & clay
520	527	7	Sand
527	555	28	Sand Stone Water at 550
555	560	5	White clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 550 to 560 ft.

Other aquifers _____

First water at 550 feet.

Casing perforated from 480 to 560 ft.

Size of perforations 3/16" x 10"



