State X

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 54139
Rec. 19
Well No. .....
Permit No. .....
Do not fill in

I

Owner ~~Jim~~ GLEN Rawson Driller S.R. McKinney & Sons, Inc.

Address 1115 Melville Drive Address Las Vegas, Nevada Lic. No. 45

Location of well: SW ¼ SE ¼ Sec 36, T20 N/S, R 60E, in Clark County

or .....

Water will be used for Domestic Total depth of well 300 feet

Size of drilled hole 12" to 50', 10" to 185' 8" to 200' Weight of casing per linear foot 3/16"

Thickness of casing 3/16" Temp. of water .....

Diameter and length of casing 8 5/8" OD form 0 to 300 feet
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface 130 feet

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well 6/27/61 Date of completion of well 7/12/61

Type of well rig Bucyrus Erie 60 L

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	clay & gravel
2	15	13	caliche
15	16	1	clay
16	25	9	gravel
25	85	60	gravley clay
85	90	5	sandy clay
90	93	3	gravel
93	130	37	gravely clay
130	145	15	sandy clay
145	155	10	cement gravel
155	177	22	cement gravel(water)
177	195	18	cement gravel
195	200	5	cement gravel(water)
200	270	70	cement gravel
270	272	2	cement gravel(water)
272	290	18	cement gravel
290	300	10	cement gravel(Water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 290 to 300 ft.

Other aquifers 270 to 272'
195 to 200'
155 to 177'

First water at 155 feet.

Casing perforated

from 223 to 300 ft.

Size of perforations

3/16" x 10"

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 5/8"OD	0	300	300'	Cemented casing in place with 2½ yards of cement at 50 feet.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailed 35 GPM at 135 feet.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed S.R. McKinney & Sons, Inc.
Well Driller

By J.L. McKinney
J.L. McKinney
License No. 45

Dated 12/11, 19 61

(Not to be filled in by Driller)