

Plugged 12/22/64 JRC

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 54140  
 Rec.....  
 Well No.....  
 Permit No.....  
*Do not fill*



Owner Pearl Toler Driller Effinger Bros.

Address Box 81 North Las Vegas, Nev. Address 212 Anderson Lane Lic. No. 105

Location of well: 1/4 Sec. 1/4, T. N/S, R. E, in Clark County

or N1/4SW1/4 Section 14 T20S R61E

Water will be used for Domestic Total depth of well 152 feet

Size of drilled hole 10 Inch Weight of casing per linear foot 9.4 lbs

Thickness of casing 9 Gauge Temp. of water.....

Diameter and length of casing 6 5/8" OD 152 feet  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 32'3" from top of casing

If flowing well describe control works.....  
 (Type and size of valve, etc.)

Date of commencement of well May 7, 1954 Date of completion of well May 13, 1954

Type of well rig "71 Speed Star"

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	15	15	Gravel
15	18	3	Red Clay
18	21	3	Limestone
21	38	17	Yellow Sandy Clay
38	41	3	Limestone
41	68	27	Yellow Sandy Clay (Water)
68	107	39	Red Sandy Clay
107	113	6	Limestone
113	115	2	White Clay
115	127	12	Yellow Clay
127	134	7	Limestone
134	147	13	Yellow Clay
147	150	3	Red Clay
150	152	2	Gravel (Water)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 150 to 152 ft.

Other aquifers.....

First water at 41 feet.

Casing perforated

from 72 to 152 ft.

Size of perforations

1/8" X 12"



