States Exhibit 1

WELL LOG AND REPORT TO THE ENGINEER OF NEVADA

54/159

Do not write in this space

Owner: Minnie Sullivan Driller: Nevada Pump & Supply Co.

Address: 143 ater Street, Henderson, Nev. Address: Las Vegas, Nevada Lic. No. 133

Location of well: SE ¼ SW ¼ Sec. 36, T. 20 S/S, R. 60 E, in Clark County

or

Water will be used for: Domestic Total depth of well: 150 feet

Size of drilled hole: 12" Weight of casing per linear foot: 12 lbs.

Thickness of casing: 10 gauge Temp. of water:

Diameter and length of casing: 150' x 8"
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 45 feet

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: May 10, 1955 Date of completion of well: May 18, 1955

Type of well rig: Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Top Soil
3	7	4	Boulders
7	45	38	Sand & Red Clay
45	50	5	Caliche
50	95	45	Red Clay
95	100	5	Sand-Little Water
100	120	20	White & Red Clay mixed
120	135	15	Sand & Gravel
135	147	12	Sand-Gravel-Water
147	150	3	Clay & Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 135 to 147 ft.

Other aquifers: 95 - 100

First water at: 45 feet

Casing perforated

from 120 to 150 ft.

Size of perforations

1/16" x 6"

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness feet	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	0	150	150	50 feet cement grout 100 feet washed pea gravel fill

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc

20 gpm at 60 feet pumping level

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed NEVADA PUMP & SUPPLY COMPANY
Well Driller

By Thos. P. Bruyn

License No.

Dated MAY 19, 19

(Not to be filled in by Driller)