WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 54159
Rec. ..... 19..
Well No. .....
Permit No. .....
Do not fill

Owner: Mike Mueblow Driller: Mike Mueblow

Address: 1110 Bonanza Address: 230 Tonopah Vegas Heights Lic. No. 138

Location of well: N.W. ¼ N.E. ¼ Sec. 16, T. 20 S, R. 61 E, in Las Vegas Vegas Heights County

or Clark

Water will be used for: Domestic Total depth of well: 200 ft

Size of drilled hole: 10 in for 57 ft rest 7 in Weight of casing per linear foot: 6 lbs

Thickness of casing: 10 gauge Temp. of water: 60

Diameter and length of casing: 8 in OD length 57 ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface: 20 ft

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well: Jan 14 1952 Date of completion of well: Jan 24 1952

Type of well rig: Home made Cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	blow sand
3	8	5	dark clay
8	24	16	light clay
24	43.6	19.6	light red clay
43.6	44.6	1	cletchie
44.6	57	13½	light red clay
57	58	1	cletchie
58	75	17	light red clay
75	76	1	cletchie
76	110	34	light clay streaks of hard clay
110	164	54	soft red clay
164	165	1	streaks of cletchie
165	170	5	soft red clay
170	190	20	hard white clay
190	195	5	soft red clay
195	197	2	cletchie and white clay
197	200	3	red soft clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 197 to 200 ft.

Other aquifers 58 ft

some water

if any more note

known

First water at 45 feet.

Casing perforated

from ..... to ..... ft.

Size of perforations

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 in	0	57	58½	Put 3 sacks of cement in bottom of hole with dump bailer set pipe in it and filled out side of casing with pea gravel and cement.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Did not pump.
Water reported to be a little hard.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Merle Meadlow
Well Driller

By Merle Meadlow

License No. 138

Dated Feb 16, 1953

(Not to be filled in by Driller)