WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 54138
Rec. 19
Well No.
Permit No.
Do not fill in

Owner: Lee Bowman Driller: Robert J. Sandlein

Address: 15 Washington Henderson Nevada Address: Lic. No. 130

Location of well: ¼ ¼ Sec. 16, T. 20 S/S, R. 62 E, in Clark County

or N½ of the N½ of the N½ of the SW¼ of the SW¼

Water will be used for: domestic Total depth of well: 124 feet

Size of drilled hole: 12 in Weight of casing per linear foot:

Thickness of casing: 16 Gauge Temp. of water:

Diameter and length of casing: 8" in casing 124 feet long

(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 60 feet

If flowing well describe control works:

(Type and size of valve, etc.)

Date of commencement of well: July 17, 1958 Date of completion of well: 24 July, 1958

Type of well rig: rotary

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	6	6	silt gravel
6	22	16	Heavy cobbles
22	34	12	sand Rock
34	45	11	soft white clay
45	72	27	soft Brown clay
72	74	2	caliche
74	78	4	Gravel Rock
78	103	25	Hard clay
103	124	21	Soft clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 74 to 78 ft.

Other aquifers 34 feet

First water at 34 feet.

Casing perforated

from 84 to 124 ft.

Size of perforations

¼ in.

919