

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55199  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Francis F. Coonrod Driller Nevada Pump & Supply Co.  
 Address 822 Park Paseo, Las Vegas, Nev. Address 412 S. 4th, Las Vegas, Nev. Lic. No. 133  
 Location of well: NW 1/4 NW 1/4 Sec. 1, T21N/S, R60E, in Clark County  
 or \_\_\_\_\_  
 Water will be used for Domestic Total depth of well 140 feet  
 Size of drilled hole 12" Weight of casing per linear foot 11.6  
 Thickness of casing 10 ga. Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" x 140'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 95'  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well Jan. 21, 1955 Date of completion of well Jan. 22, 1955  
 Type of well rig Cable Tools

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Top Soil
5	13	8	Caliche
13	67	54	Sandy Clay
67	117	50	Clay
117	140	23	Sand Gravel Water Bearing
<del>117</del>			

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 117 to 140 ft.  
 Other aquifers \_\_\_\_\_

---

First water at 117 feet.

Casing perforated  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations \_\_\_\_\_

