


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55240
 Rec. 19...
 Well No.
 Permit No.
Do not fill in



Owner J. C. Ledbetter Driller NEVADA PUMP & SUPPLY CO.
 Address P. O. Box 851, Blue Diamond, Nev. Address 412 S. 4th St., Las Vegas Lic. No. 133
 Location of well: NW 1/4 SE 1/4 Sec. 1, T. 21N/S, R. 60E, in Clark County
 or West Charleston
 Water will be used for Domestic Total depth of well 160 feet
 Size of drilled hole 12" Weight of casing per linear foot 9 lb.
 Thickness of casing 12 ga. Temp. of water
 Diameter and length of casing 8" x 160'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure
 If nonflowing well give depth of standing water from surface 80 feet
 If flowing well describe control works
 (Type and size of valve, etc.)
 Date of commencement of well Dec. 6, 1954 Date of completion of well Dec. 9, 1954
 Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Surface soil
3	40	37	Conglam. & White Clay
40	85	45	Rock & Brown Clay
85	88	3	Sand-Brown-Little water
88	117	29	Brown Clay & rock ledges
117	125	8	Sand-Water & gravel
125	150	25	Clay & Rock ledges
150	158	8	Gravel & Sand
158	160	2	Clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 117 to 125 ft.
 Other aquifers 150 - 158
85 - 88

First water at 85 feet.

Casing perforated
 from 100 to 160 ft.

Size of perforations
1/16 x 6"



