

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55250
 Rec. 19
 Well No.
 Permit No.
Do not fill in

Owner Fletcher Mount Driller Patrick H. Thompson

Address 1466 Westwind Rd. Las Vegas, Nev. Address 217 S. 26th St. L.V.N. Lic. No. 192

Location of well: NE 1/4 NE 1/4 Sec. 1, T. 21 N/S, R. 6 E, in Clark County

or

Water will be used for Domestic Total depth of well 300

Size of drilled hole 12" to 50' - 10" from 50 to 300' Weight of casing per linear foot 12#

Thickness of casing 10 guage Temp. of water Cool

Diameter and length of casing 8" dia. 301' length
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 140'

If flowing well describe control works

(Type and size of valve, etc.)

Date of commencement of well July 23, 1959 Date of completion of well July 31, 1959

Type of well rig Cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	7	7	sand & clay
7	12	5	caliche
12	160	148	brown cement gravel
160	164	4	soft brown sand little water
164	170	6	white cement gravel
170	175	5	loose gravel Water
175	260	85	white cement gravel
260	264	4	loose gravel Water
264	290	26	white cement gravel
290	294	4	loose gravel Water
294	300	6	white cement gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 170 to 175 ft.

Other aquifers 260 - 264

290 - 294

First water at 160 feet.

Casing perforated

from 170 to 300 ft.

Size of perforations

1/8 x 12 - 4 rows



