

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55263  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner S. R. McKinney & Driller S. R. McKinney & Son  
 Address 1042 S. Main Las Vegas Address 1042 S. Main Las Vegas Lic. No. 45  
 Location of well: SW 1/4 NE 1/4 Sec. 19, T. 20 N/S, R. 62 E, in Clark County \_\_\_\_\_

Water will be used for Domestic Total depth of well 125 ft.

Size of drilled hole 12" to 55 ft., 8" to 125 Weight of casing per linear foot 28 lb.

Thickness of casing 5/16" Temp. of water \_\_\_\_\_

Diameter and length of casing 8" I. D. to 60 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 35 ft

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Sept 24, 1952 Date of completion of well Sept 25, 1952

Type of well rig Bucyrus Erie 24 L. Spudier

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	15	15	Sandy clay
15	25	10	Sand and Gravel
25	40	15	Sandy clay
40	45	5	Red sand Water
45	65	20	Red Sandy clay
65	70	5	Red sand Water
70	90	20	Red sandy clay
90	97	7	Red sand water
97	115	18	Red clay
115	120	5	Sand and gravel Water
120	125	5	Red sandy clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 90 to 97 ft.

Other aquifers 115 to 120

65 to 70

First water at 40 feet.

Casing perforated

from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations

