


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 55285  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*



Owner Jim MENING Driller CHARLIE CRIBBS 70

Address 2104 glider NLV. Address GEN. DEL. Lic. No 70

Location of well: NW 1/4 NE 1/4 Sec. 19., T. 20N/S, R. 62E, in CLARK County

or well is located at 2370 walnut N.L.V.

Water will be used for domestic ic Total depth of well 200 ft

Size of drilled hole 12 Weight of casing per linear foot \_\_\_\_\_

3/16

Thickness of casing \_\_\_\_\_ Temp. of water \_\_\_\_\_

8 5/8 200 ft.

Diameter and length of casing \_\_\_\_\_  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 55

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well June 19 Date of completion of well 6 /21

Type of well rig SPUDDER

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
000	5	5	silt & sand
5	25	20	cement gravel
25	55	30	white clay little water at 50
55	110	55	brown clay
110	115	5	conglomerate some water
115	165	50	brown clat
165	185	20	white clay ribs of decomposed lime bearing water
185	200	15	brown clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)  
 from 165 to 185 ft.

Other aquifers 110

First water at 55 feet.

Casing perforated  
 from 100 to 200 ft.

Size of perforations  
1/4 X 6

