

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55308  
 Rec. .... 19...  
 Well No. ....  
 Permit No. ....  
*Do not fill in*

Owner James R. & Daisy B. Watson Driller Effinger Bros.  
 Address 808 Biltmore Drive Address 212 Anderson Lane Lic. No. 105  
 Location of well: 1/4 Sec. 1/4, T. N/S, R. E, in Clark County  
 or E 1/4 NW 1/4 SW 1/4 Section 1 T21S R60E  
 Water will be used for Domestic Total depth of well 200 feet  
 Size of drilled hole 12 Inch Weight of casing per linear foot 12.06 lbs.  
 Thickness of casing 10 Guage Temp. of water.....  
 Diameter and length of casing 8 5/8" OD 200 feet  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure.....  
 If nonflowing well give depth of standing water from surface 115' from top of casing  
 If flowing well describe control works.....  
 (Type and size of valve, etc.)  
 Date of commencement of well December 3, 1954 Date of completion of well December 14, 1954  
 Type of well rig "71 Speed Star"

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Limestone
3	12	9	Gravel
12	17	5	Limestone
17	45	28	Cement Gravel
45	55	10	White Clay
55	68	13	Cement Gravel
68	75	7	Gravel
75	98	23	Limestone
98	108	10	Gravel
108	127	19	Fine Gravel
127	133	6	Limestone
133	139	6	Gravel
139	147	8	Cement Gravel
147	200	53	Gravel (Water)

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 147 to 200 ft.

Other aquifers.....

---

First water at 147 feet.

Casing perforated

from 140 to 200 ft.

Size of perforations

1/8" X 12"

