X

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 55312
Rec. 19
Well No. .....
Permit No. .....
Do not fill in

Owner W.H.Wiseman Driller C.Cribbs

Address 6588 Valley Vw Address 2710 Palimeno Lane Lic. No. 70

Location of well: SW ¼SW ¼ Sec. 1, T21N/S, R60 E, in Clark County

or Betwene Westwind & Jones.(Near far out acers)

Water will be used for Domestic Total depth of well 275 Ft

Size of drilled hole 12" Weight of casing per linear foot 16

Thickness of casing 10 Ga Temp. of water

Diameter and length of casing 8 5/8 x 275ft
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 170

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 4/30/164 Date of completion of well 5/11 64

Type of well rig spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
00	75	75	Caliche
75	100	25	Red clay
100	190	90	Cement Gravel
			First water strata
190	250	60	Cement gravel
250	275	25	Water & gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 250 to 275 ft.

Other aquifers

First water at 190 feet.

Casing perforated

from 175 to 275 ft.

Size of perforations

¼x6

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 5/8			275	Gravelpacked & Cemented with 3 1/2 YDS Cement

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Charley Coribbs
Well Driller

By

License No. 70

Dated 5 X/11, 1964

(Not to be filled in by Driller)

RECEIVED
MAY 26 1964
DIV. OF WATER RESOURCES
BRANCH OFFICE
LAS VEGAS, NEVADA