WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55359
Rec. 19
Well No.
Permit No.
Do not fill in

Owner: CARL BOYDEN
Driller: J.E. HOWARD & SON

Address: 1023 Laurel Drive, LV Nev.
Address: 2600 Webb St., N.LV Nev. Lic. No. 205

Location of well: W½ NW¼ NE¼ SW¼ Sec. 11, T. 21 N/S, R. 60 E, in Clark County

or

Water will be used for: domestic
Total depth of well: 215 ft.

Size of drilled hole: 8" (12" to 50 ft.)
Weight of casing per linear foot: 25#

Thickness of casing: 1/4"
Temp. of water:

Diameter and length of casing: 8" - 216 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 176 ft.

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: 5/30/55
Date of completion of well: 6/17/55

Type of well rig: Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	60	60	Conglomerate
60	70	10	Sandy Clay
70	100	30	Conglomerate
100	120	20	Red Sandy Gravel
120	215	95	Conglomerate

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 190 to 205 ft.

Other aquifers:

First water at 189 feet.

Casing perforated
from 175 to 215 ft.

Size of perforations
1/4" x 8"

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness		Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"	0	215	216	Casing extends 1 ft above ground - cemented to a depth of 50 feet 13/4 yd - gravel pack below

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailer Test - 20 gal per min - pulls down to 181 ft.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Nolan Howard
Well Driller

By

License No. 205

Dated June 20, 19 55

(Not to be filled in by Driller)