

**WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA**

Log No. 55373
 Rec. 19
 Well No. _____
 Permit No. _____
Do not fold in

Owner W. F. Fulford Driller S. R. McKinney & Son

Address 58 Sweab St. Nellis Air Base, Las Vegas, Nevada Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: NW 1/4 SE 1/4 Sec. 11, T21 N/S, R60 E, in Clark County

or West 1/2 of SW 1/2 of NW 1/2 of SE 1/2 of Section 11, Twp 21, Range 60 East

Water will be used for Domestic Total depth of well 202

Size of drilled hole 12" to 50 ft, 10" to 202 Weight of casing per linear foot 20 lb.

Thickness of casing 1/4" Temp. of water _____

Diameter and length of casing 8" I.D. to 202
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 160 ft.

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well Feb. 25, 1955 Date of completion of well March 2, 1955

Type of well rig 72 Speed Star, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	25	25	cemented gravel
25	36	11	caliche
36	55	19	cemented gravel
55	85	30	caliche
85	92	7	cemented gravel
92	125	33	caliche
125	165	40	cemented gravel
165	175	10	sand and gravel
175	180	5	sand water
180	192	12	gravel water
192	202	10	sand and gravel water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 192 to 202 ft.

Other aquifers 175 to 192

First water at 175 feet.

Casing perforated

from 162 to 202 ft.

Size of perforations

3/16" X 10"

