

stall  
x

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 55415  
Rec. \_\_\_\_\_ 19\_\_\_\_  
Well No. \_\_\_\_\_  
Permit No. \_\_\_\_\_  
*Do not fill in*



Owner C.P. Sloniger Driller S.R. McKinley & Sons, Inc.

Address 2187 Walnut Road Address 1042 So. Main St. Lic. No. 45

Location of well: SE 1/4 NW 1/4 Sec. 19, T. 20 N/S, R. 62 E, in Clark County

or \_\_\_\_\_

Water will be used for Domestic Total depth of well 200 feet

Size of drilled hole 10", reamed 12" to 50 feet Weight of casing per linear foot 10 ga.

Thickness of casing 10 gauge Temp. of water \_\_\_\_\_

Diameter and length of casing 8" x 200 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 50 feet

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 6/24/60 Date of completion of well 6/28/60

Type of well rig Bucyrus Erie, 24J Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	15	15	Clay
15	17	2	gravel
17	31	14	clay
31	32	1	gravel
32	65	33	gray clay, gritty
65	70	5	brown clay
70	95	25	gray clay
95	115	20	brown sandy clay-water
115	125	10	brown clay
125	135	10	sandy clay-water
135	160	25	brown clay
160	165	5	brown sandy clay
165	180	15	brown clay
180	185	5	brown sandy clay-water
185	200	15	brown cly & sandstone streaks

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
from 180 to 200 ft.

Other aquifers 95-135

---

First water at 95 feet.

---

Casing perforated  
from 100 to 140 ft.  
180 to 200

---

Size of perforations  
3/16" x 10"



