

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55486
 Rec. _____ 19____
 Well No. _____
 Permit No. _____
Do not fill in

Owner Harry L. Lindell Driller S. R. McKinney & Son

Address Arville & Charleston, Corridor #15 Address 1042 S. Main Las Vegas Lic. No. 15

Location of well: NE 1/4 NW 1/4 Sec. 12, T. 21N/S, R. 60E, in Clark County

or East 1/2 of NW 1/2 of NE 1/4 of NW 1/4 of Section 12, Twp 21, Range 60 E.

Water will be used for Domestic Total depth of well 160 ft.

Size of drilled hole 12" to 50 ft., 10" to 160 Weight of casing per linear foot 28 lb.

Thickness of casing 1/4" Temp. of water _____

Diameter and length of casing 8" I.D. to 160 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 105 ft.

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well January 25, 1955 Date of completion of well January 20, 1955

Type of well rig Bucyrus Erie 24 L, Scudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	caliche
3	16	13	white clay
16	50	34	gravel
50	59	9	brown clay
59	62	3	caliche
62	73	11	sand and gravel
73	76	3	brown clay
76	85	9	sand and gravel
85	88	3	gravel
88	103	15	brown clay
103	106	3	caliche
106	113	7	brown clay
113	115	2	caliche
115	119	4	brown clay
119	121	2	caliche
121	124	3	brown sand water
124	127	3	gravel water
127	131	4	red sand water
131	153	22	gravel water
153	156	3	red sand water
156	160	4	cemented gravel water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 121 to 160 ft.

Other aquifers _____

First water at 121 feet.

Casing perforated
3x18" 110 160
 from _____ to _____ ft.

3/16" Size of perforations x 10"

