

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55494
 Rec. 19
 Well No. _____
 Permit No. _____
Do not fill in

Owner John M. Lindsay Driller Nevada Pump & Supply Company
 Address 1350 Davidson Way, Reno, Nevada Address Las Vegas, Nevada Lic. No. 133
 Location of well: NW¹/₄ NW¹/₄ Sec. 12., T. 21 N/S, R. 60 E, in Clark County
 or _____
 Water will be used for Domestic Total depth of well 168 feet
 Size of drilled hole 12" Weight of casing per linear foot 12 lbs.
 Thickness of casing 10 gauge Temp. of water _____
 Diameter and length of casing 8" x 168'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 130 feet
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well April 13, 1955 Date of completion of well April 15, 1955
 Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	1	1	Top Soil
1	5	4	Caliche
5	15	10	Gravel
15	25	10	Caliche
25	35	10	Gravel
35	58	23	Caliche
58	70	12	Cemented Gravel & Clay
70	78	8	Caliche
78	98	20	Sandy Clay
98	100	2	Gravel & Clay
100	122	22	Sandy Clay-Water Bearing
122	140	18	Sandy Clay
140	154	14	Sandy Clay with Gravel-Water
154	168	14	Clay and Gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 140 to 154 ft.

Other aquifers 100 - 122

First water at 108 feet.

Casing perforated

from 90 to 168 ft.

Size of perforations

1/16" x 6"



