WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55518
Rec. 19
Well No.
Permit No.
Do not fill in

Owner CHESTER J BOLES Driller Joseph C Metz
Address 2966 E COLLEGE AVE Address Las Vegas Lic. No. 35
Location of well: NW¼ SW¼ Sec. 20 T 20 N/S, R 62 E, in Clark County
or
Water will be used for Domestic Total depth of well 120
Size of drilled hole 6" Weight of casing per linear foot 12#
Thickness of casing 3/16 Temp. of water 68
Diameter and length of casing 6" I.D. x 58'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface 37'
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well Nov 10-1954 Date of completion of well Nov 26-1954
Type of well rig spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
–	29	29	silt
29	37	8	gravel
37	39	2	sand (W)
39	42	3	gravel
42	62	20	clay
62	65	3	gravel (W) 5½ GPM
65	99	34	clay
99	104	5	soft lime
104	108	4	hard lime
108	112	4	soft lime
112	116	4	broken lime (W)
116	120	4	clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 112 to 116 ft.
Other aquifers 62-65

First water at 37-39 feet.

Casing perforated
from — to — ft.

Size of perforations

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6" I.D.	1" above	57'	58'	cemented to bottom of casing

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

15 G.P.M. drawdown to 55'
20 " " 60
25 " " 65

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Joseph E. Metz
Well Driller

By Jean

License No. 35

Dated Nov 23, 1954

(Not to be filled in by Driller)