

**WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA**

Log No. 55529
 Rec. 6/29 1955
 Well No. _____
 Permit No. _____
 Do not fill in

Owner Gene Rohde Driller S.R. McKinney & Son

Address _____ Address 1042 So. Main St. L.V. Lic. No. 45

Location of well: SW 1/4 SW 1/4 Sec. 12, T. 21 N/S, R. 60 E, in Clark County
 or W 1/2 of NE 1/4 of SW 1/4 of SW 1/4 of Sec 12, Twp. 21, Range 60

Water will be used for Domestic Total depth of well 190'

Size of drilled hole 12" to 50' 10" to 190' Weight of casing per linear foot 10 guage

Thickness of casing 10 Guage Temp. of water _____

Diameter and length of casing 8" I.D. to 190'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 120'

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well June 22, 1955 Date of completion of well June 24, 1955

Type of well rig Bucyrus Erie 24L, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	40	40	Cement
40	48	8	Clay
48	55	7	Sand
55	105	50	Sandy Clay
105	115	10	Sand
115	125	10	Sandy clay water
125	140	15	Sandy clay
140	165	25	Sandy clay water
165	170	5	Sand
170	180	10	Sandy & Clay
180	190	10	Sand & Gravel water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 180 to 190 ft.

Other aquifers 140' to 165'
115' to 125'

First water at 115 feet.

Casing perforated

from 150 to 190 ft.

Size of perforations

3/16" x 10"



