


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

2833

Log No. **55542**  
 Rec. \_\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_

*Do not fill in*



Owner **J. FRED SCHWARTZ & THELMA G.** Driller **Charlie Cribbs** **70**  
**S.B. Rodgers** **158**  
 Address **Las Vegas Nev.** Address **300 Delomino Lane** Lic. No. \_\_\_\_\_  
**Las Vegas Nev** **CLARK** County \_\_\_\_\_

Location of well:  $\frac{1}{4}$   $\frac{1}{4}$  Sec. \_\_\_\_\_, T. \_\_\_\_\_ N/S, R. \_\_\_\_\_ E, in \_\_\_\_\_ County  
 or **E 1/4 SW 1/4 SW 1/4 Sec 12 T 21 R 50 E**  
**domestic**

Water will be used for \_\_\_\_\_ Total depth of well **180 ft.**

Size of drilled hole **12** Weight of casing per linear foot **14**

Thickness of casing **10 gauge** Temp. of water \_\_\_\_\_

Diameter and length of casing **8 5/8 50 L**  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface **103**

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_

Date of commencement of well **April 3** Date of completion of well **4 / 5 / 55**

Type of well rig **SPUDDER**

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
00	2	2	sand and gravel
2	3	4	caliche
3	45	39	brown sandy clay
45	50	5	cement gravel
50	120	70	brown sandy clay
120	125	5	sand soft some water
125	175	50	brown sandy clay
175	180	5	sand gravel & WATER
			Total depth 180

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation) **175** **180**  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.  
**120**

Other aquifers \_\_\_\_\_

\_\_\_\_\_ **120**

First water at \_\_\_\_\_ feet.

Casing perforated **180** **180**  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.  
**1/8 X 6in.**

Size of perforations \_\_\_\_\_

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
95/8	00	180	20 L.	180 ft well casing gravelpacked from bottom up to 50 ft. cemented from surface to 50 f. 1 1/2 yds. Ready mix concrete

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

---



---



---



---



---



---



---



---

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Charlie Oulley  
Well Driller

By L. B. Redman

License No. 70 & 156

Dated April 5, 1952

(Not to be filled in by Driller)

---



---



---



---



---



---



---



---



---



---