


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55550  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*



Owner Lucille Womack Driller Bert Hargrave  
 Address \_\_\_\_\_ Address Edwards Lic. No. 63  
 Location of well:  $\frac{1}{4}$   $\frac{1}{4}$  Sec. 22, T. 21 S., R. 60 E., in Clark County  
 or W  $\frac{1}{4}$  SW  $\frac{1}{4}$  NW  $\frac{1}{4}$  NE  $\frac{1}{4}$   
 Water will be used for Pomestor Total depth of well 180  
 Size of drilled hole 10" Weight of casing per linear foot 26#  
 Thickness of casing 1/4 Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8" - 180  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 75 - foot  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well Nov. 20 - 54 Date of completion of well Nov. 30 - 54  
 Type of well rig 71 steel

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Surface
3	5	2	Hard Rock
5	<del>30</del>	25	clay and gravel
30	35	5	Rock
35	110	75	Gravel & clay water
110	120	10	Gravel - water
120	160	40	clay & gravel
160	180	20	Gravel - water

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 160 to 180 ft.

Other aquifers \_\_\_\_\_

First water at 110 feet.

Casing perforated  
 from 100 to 180 ft.

Size of perforations  
1/2" - 12" Long

