

STATE  
X

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55658

Rec. \_\_\_\_\_ 19\_\_

Well No. \_\_\_\_\_

Permit No. \_\_\_\_\_

Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Gustave W. Hahn Driller S. R. McKaney & Sons, Inc.

Address 5061 Judson Address 0042 So. Main St. Lic. No. 45

Location of well: SE 1/4 NE 1/4 Sec. 20, T. 20N/S, R. 62E, in Clark County

Water will be used for Domestic Total depth of well 200'

Size of drilled hole 12" to 50' 10" to 200' Weight of casing per linear foot 188

Thickness of casing .188 Temp. of water \_\_\_\_\_

Diameter and length of casing 8" to 200'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 60'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 4/4/66 Date of completion of well 4/7/66

Type of well rig Bucyrus Erie 225

## LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	28	28	Clay with Gravel Streaks
28	53	25	Brown Clay & Gravel
53	60	7	White Clay
60	75	5	Brown Clay (Water)
75	100	25	White Clay
100	125	25	Brown Clay (Water)
125	135	10	White
135	200	65	Clay & Gravel (Water)

## Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 135' to 200 ft.

Other aquifers 100' to 125'

60' to 75'

First water at 60' feet.

Casing perforated

from 60' to 200 ft.

Size of perforations

3/16 X 10"

