WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55665
Rec. 19
Well No. .....
Permit No. .....
Do not fill in

Owner: Roft O. Compton Driller: S R McKinney & Son

Address: Genl. Del. Las Vegas, Nev. Address: 1042 So. Main Lic. No. 45

Location of well: ¼ ¼ Sec. 13, T. 21 N/S, R. 61 E, in Clark County

or .....

Water will be used for: Domestic Total depth of well: 160'

Size of drilled hole: 8' Weight of casing per linear foot: 28#

Thickness of casing: 5/16" Well Temp. of water .....

Diameter and length of casing: 60 feet of 8 5/8" O.D.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: 8 g.p.m.

If nonflowing well give depth of standing water from surface .....

If flowing well describe control works: Cap with plate - 1" Valve
(Type and size of valve, etc.)

Date of commencement of well: Dec 10 - 52 Date of completion of well: Dec 13 - 52

Type of well rig: Bucyrus Erie Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Sand
8	25	17	Brown Clay
25	33	8	Gravel - Water
33	45	7	White Clay
45	50	5	Red Sand
50	70	20	red sandy clay
70	75	5	red sand Little wtr.
75	105	30	red sandy clay
105	115	10	Sandy Clay
115	121	6	Limestone
121	125	4	Red Sandstone
125	147	22	Sandy Clay
147	155	8	Water - Red Sandstone
155	160	5	red sandy clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 147 to 155 ft.

Other aquifers 70 - 75

25 - 33

First water at 25 - 33 feet.

Casing perforated

from none to ..... ft.

Size of perforations

(OVER)