

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. <b>55677</b>
Rec. <b>19</b>
Well No. _____
Permit No. _____

Do not fill in

Owner JESSE LEE DOSS Driller LOUIS F. EVANS

Address 3025 LA CANADA LAS VEGAS, NEVADA Address 2020 CARROLL N. LAS VEGAS Lic. No. 117

Location of well: S.E. 1/4 SE 1/4 Sec. 13., T. 21 N/S, R. 61 E, in CLARK County \_\_\_\_\_  
or \_\_\_\_\_

Water will be used for DOMESTIC Total depth of well 200 ft.

Size of drilled hole 50' 12" 150' 10" Weight of casing per linear foot 12.50 lbs.

Thickness of casing 1.0 ga. Temp. of water \_\_\_\_\_

Diameter and length of casing 3.5/8" O.D. 200'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 35 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well AUG. 23, 1963 Date of completion of well AUG. 30, 1963

Type of well rig KEYSTONE CABLE TOOL

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	sand
5	15	10	cement gravel
15	25	10	clay & gravel
25	50	25	brown clay (water)
50	55	5	cement gravel
55	65	10	clay & gravel
65	75	10	brown clay (water)
75	80	5	clay & gravel (water)
80	90	10	sand
90	100	10	brown clay (water)
100	110	10	sand & clay
110	120	10	brown clay (water)
120	125	5	clay & gravel (water)
125	130	5	brown clay (water)
130	135	5	clay & gravel (water)
135	150	15	brown clay (water)
150	155	5	cement gravel
155	170	15	clay & gravel (water)
170	175	5	cement gravel
175	200	25	clay & gravel (water)

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 110 to 150 ft.

Other aquifers 65 to 80  
90 to 100 155 to 170  
175 to 200

---

First water at 45 feet.

Casing perforated

from 60 to 200 ft.

Size of perforations

1/4" wide 6" long



LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	Remarks—Seals, Grouting, Etc.
8 5/8"	0	200	200	GRAVEL PACKED 150 FT.FROM 50 ft. to 200 ft. 3 yds.gravel CEMENTED 50 FT.FROM 0 to 50 ft. 2 yds.cement

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

---



---



---



---



---



---

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Louis F. Evans  
Well Driller

By LOUIS F. EVANS

License No. 117

Dated Sept. 24, 19 63

(Not to be filled in by Driller)

---



---



---



---



---



---



---



---



---



---

RECEIVED

SEP 26 1963

DIV. OF WATER RESOURCES  
BRANCH OFFICE  
LAS VEGAS, NEVADA