

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55729  
 Rec. 110  
 Well No. 117  
 Permit No. 117  
*Do not fill in*

Owner Harry P. Starkey Driller Louis F. Evans  
 Address 2981 E. Swain, L.O., NV 89121 Address 2020 Carroll N. Las Vegas Lic. No. 117  
 Location of well: 1/4 S.W. 1/4 Sec. 13, T. 21 N/S, R. 61 E, in Clark County  
 or \_\_\_\_\_  
 Water will be used for Domestic Total depth of well 180 ft.  
 Size of drilled hole 60 ft. 10 inch. 120 ft. 8 inch. hole Weight of casing per linear foot 11.6  
 Thickness of casing 10 gauge Temp. of water \_\_\_\_\_  
 Diameter and length of casing 8 inch. O.D. pipe 60 ft.  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure 1 gal. per min.  
 If nonflowing well give depth of standing water from surface \_\_\_\_\_  
 If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.) \_\_\_\_\_  
 Date of commencement of well Apr. 28, 1953 Date of completion of well Apr. May 2, 1953  
 Type of well rig Armstrong

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	sand
2	4	2	gray clay
4	6	2	rock
6	30	24	yellow clay
30	49	19	yellow clay & gravel (water)
49	60	11	yellow clay
60	65	5	gray clay
65	170	105	red sandy clay
170	178	8	gravel (water)
178	180	2	red clay

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 170 to 178 ft.  
 Other aquifers 30 to 49

---

First water at 30 feet.

---

Casing perforated  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.

---

Size of perforations \_\_\_\_\_

