


# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55828  
 Rec. No. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*



Owner John Sherwin Driller S. R. McKinney & Son  
 Address 904 Hassett, Las Vegas Address 1042 S. Main Las Vegas Lic. No. 45  
 Location of well: NE 1/4 SW 1/4 Sec. 20, T. 20N/S, R62 E, in Clark County \_\_\_\_\_  
 or \_\_\_\_\_

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 12" to 50 ft., 8" to 100 ft. Weight of casing per linear foot 10 guage

Thickness of casing 10 guage Temp. of water \_\_\_\_\_

Diameter and length of casing 8" I.D. to 60 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 42 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well Nov. 17, 1954 Date of completion of well Nov. 18, 1954

Type of well rig Bucyrus Erie 24 L, Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	1	1	topsoil
1	45	44	brown clay
45	57	12	gravel water
57	71	14	white clay
71	76	5	white sand water
76	83	7	brown clay
83	89	6	brown sand water
89	100	11	white clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)  
 from 83 to 89 ft.  
 Other aquifers 71 to 76  
50 to 57

First water at 45 feet.

Casing perforated  
 from none to \_\_\_\_\_ ft.

Size of perforations \_\_\_\_\_



