

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA

Log No. 55912
 Rec. 19
 Well No. _____
 Permit No. _____
 Do not fill in

Owner Nolan Lee Driller H. H. Smith
 Address Pyris Acton Address 1819 Decatur Lane L.V. Lic. No. 186
 Location of well: SW 1/4 NW 1/4 Sec. 23, T21 S, R61 E, in M.D. Meridian Nevada Clark County

Water will be used for Domestic Purposes Total depth of well 160'

Size of drilled hole 10" Weight of casing per linear foot _____

Thickness of casing 10 Gauge Temp. of water _____

Diameter and length of casing 8" x 160' x (50' length)
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 30'

If flowing well describe control works _____
 (Type and size of valve, etc.)

Date of commencement of well 2/15/55 Date of completion of well 2/22/55

Type of well rig Spudger

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0'	35'	35'	Caliche
35'	50'	15'	Red Clay
50'	50'	0'	1st Water
50'	70'	20'	Red Clay (with water gravel mixed)
70'	85'	15'	Caliche
85'	115'	30'	Caliche + Red Clay
115'	115'	0'	2nd Water
115'	160'	45'	Red Clay + Water gravel

Water-bearing Formation, Casing Perforations, Etc.
Red Clay + Water Bore
 Chief aquifer (water-bearing formation)
 from 115' to 160' ft.
 Other aquifers _____
 First water at 50' feet.
 Casing perforated from 90' to 150' ft.
 Size of perforations 1/4" x 12" slots

