

State

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

55924

Log No. _____
 Rec. _____
 Well No. _____
 Permit No. _____

Do not fill in.

Owner E.D. Mantle Driller S.R. Mc Kinney & Son

Address Bond Trailer Park # 24 Address 1042 So. Main Lic. No. 45

Location of well: SE 1/4 Ne 1/4 Sec 23, T. 21N/S, R. 61E, in Clark County

or _____

Water will be used for Domestic Total depth of well 200 ft.

Size of drilled hole 12" to 50 ft. 10" to 200ft. Weight of casing per linear foot 10 Gauge

Thickness of casing 10 Gauge Temp. of water _____

Diameter and length of casing 8 5/8" O.D. from 0ft to 201 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure _____

If nonflowing well give depth of standing water from surface 14 ft.

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well 6/21/59 Date of completion of well 6/23/59

Type of well rig Bucyrus Erie 24 L.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	20	20	Clay & Gravel	
20	45	25	Sandy clay	
45	50	5	Sand & Gravel (Water)	Chief aquifer (water-bearing formation)
50	85	35	Brown sandy clay	from <u>190</u> to <u>195</u> ft.
85	90	5	Clay & Gravel	
90	125	35	Brown sandy clay	Other aquifers <u>125 to 128</u>
125	128	3	Gravel (Water)	<u>45 to 50</u>
128	190	62	Brown sandy clay	
190	195	5	Gravel (Water)	
195	200	5	Red clay	

First water at 45 feet.

Casing perforated from 180 to 200 ft.

Size of perforations 100 to 160

3/16 x 10"

