

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 55959
 Rec. 19...
 Well No.
 Permit No.
Do not fill in

Owner Thomas O. Blocker Driller S. R. McKinley Son
 Address East collere Address 1042 S. Main Las Vegas Lic. No. 45
 Location of well: NE 1/4 SE 1/4 Sec. 21, T. 20N/S, R. 62E, in Clark County

Water will be used for Domestic Total depth of well 75 ft.

Size of drilled hole 12" to 35 ft. 8" to 75 ft. Weight of casing per linear foot 20 lb.

Thickness of casing 3/16" Temp. of water.....

Diameter and length of casing 8" O.D. to 40 ft.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 35 ft.

If flowing well describe control works.....
 (Type and size of valve, etc.)

Date of commencement of well Feb. 6, 1953 Date of completion of well Feb. 7, 1953

Type of well rig Bucyrus Erie 24 L. Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Surface soil
3	7	4	Caliche
7	14	7	Red sandy clay
14	16	2	Caliche
16	46	30	White sandy clay
46	72	26	Red sandy clay Water
72	24	2	Gravel
74	75	1	Red sandy clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 46 to 72 ft.

Other aquifers 72 to 74

First water at 63 ft. feet.

Casing perforated

from None to ft.

Size of perforations

