

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 55996  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Douglas Jorgensen  
Lester E Cannon Driller Rodgers Cribbs

Address 1848 Christy Address 2710 Palimano Lic. No. 70  
156

Location of well: NW 1/4 NE 1/4 Sec 21, T. 20N/S, R62 E, in Clark County 156  
NW. 36.

Water will be used for Domestic Total depth of well 150

Size of drilled hole 12 Weight of casing per linear foot 16

Thickness of casing 1.0 GA 3/16 Temp. of water \_\_\_\_\_

Diameter and length of casing 140' 85/8  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 50

If flowing well describe control works Submersible  
 (Type and size of valve, etc.)

Date of commencement of well Feb 1 64 Date of completion of well Feb 4 64

Type of well rig Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
00	8	8	Brown silt & clay
8	48	40-48	White clay
48	50	2	Decom. Lime
50	80	30	Light B. Clay
80	85	5	White lime water
85	135	50	Brown clay
135	140	5	White lime & gravel Water
140	150	10	Pink Clay

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 135 to 140 ft.

Other aquifers \_\_\_\_\_

---

First water at 50 feet.

Casing perforated  
 from 60 to 140 ft.

Size of perforations  
1/2 x 6

