

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 56811

Rec. 19

Well No.

Permit No. 66953

Do not fill in

Owner Dr. Fouts Driller O.M. GULLARD

Address Sierra Vista-Paradise Valley Address 6044 Euclid Lic. No. 15

Location of well: SW 1/4 NW 1/4 Sec. 6, T22/N/S, R. 62E, in Clark County
 or 3555 PAMA APN 178-06-202-005

Water will be used for Domestic Total depth of well 550 ft.

Size of drilled hole 12" 300 ft. 8" 530 Weight of casing per linear foot

Thickness of casing 188 wall Temp. of water

Diameter and length of casing 8" 530 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure 5 gpm

If nonflowing well give depth of standing water from surface

If flowing well describe control works Screw on cap 2" Gate Valve
(Type and size of valve, etc.)

Date of commencement of well 5-31-63 Date of completion of well 6-22-63

Type of well rig Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	23	23	Sandy Black clay
23	24	1	Limestone-1st water
24	40	16	Soft black clay
40	165	125	Hard brown clay
165	167	2	Large rock & sand-2nd water
167	365	198	Brown clay
365	530	165	Soft & hard brown clay 2 & 3 ft apart
530	550	20	Red sandstone--water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 530 to 550 ft.
165 167

Other aquifers

First water at 24 feet.

Casing perforated

from to ft.

Size of perforations



