WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 56812
Rec. ..... 19.....
Well No. .....
Permit No. .....
Do not fill in

Owner Miss Gladys Gerber Driller S. R. McKinney & Son

Address 2019 Bonnie Ave, Las Vegas Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: NW ¼ NE ¼ Sec. 6, T. 22N/S, R. 62E, in clark County

or .....

Water will be used for Domestic Total depth of well 185 ft.

Size of drilled hole 12" to 90 ft. 8" to 185 Weight of casing per linear foot 28 lb.

Thickness of casing 5/16" Temp. of water .....

Diameter and length of casing 8" I.D. to 102 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface 18 ft

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well Sept. 18, 1953 Date of completion of well Sept. 21, 1953

Type of well rig Bucyrus Erie 24 L, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	25	25	sandy soil
25	30	5	gravel Water
30	38	8	silty sand
38	105	67	clay and gravel
105	170	65	graveley clay Water
170	185	15	cemented gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 105 to 170 ft.

Other aquifers .....

First water at 30 ft. feet.

Casing perforated

from None to ..... ft.

Size of perforations

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8" I.D.	0	102	102	8" cemented down to 90 ft. with 2 yds concrete.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

60 G.P.M. from 45 ft. bailed.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed C. R. McKenney & Son
Well Driller

By M. E. McKenney

License No. 45

Dated 11-6, 1953

(Not to be filled in by Driller)