Log No. 57019
Rec. 19
Well No. 1
Permit No. .....
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Herman Harris Driller: Patrick H. Thompson

Address: 3072 Mojave, Las Vegas, Nev. Address: 217 S. 26th St. L.V.N. Lic. No. 192

Location of well: NW¼NE¼ Sec 28, T 20 N/S, R 62 E, in Clark County

or

Water will be used for: Domestic Total depth of well: 150'

Size of drilled hole: 12" to 50' - 10" from 50 to 150 Weight of casing per linear foot: 17#

Thickness of casing: 3/16" Temp. of water: cool

Diameter and length of casing: 3/16" Dia. -- 152' length
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure: .....

If nonflowing well give depth of standing water from surface: 70'

If flowing well describe control works: .....
(Type and size of valve, etc.)

Date of commencement of well: Aug. 14, 1962 Date of completion of well: Aug. 16, 1962

Type of well rig: cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	5	5	Sandy soil
5	32	27	White clay
32	41	9	sandy white clay
41	55	14	gravel -- dry
55	70	15	brown clay
70	150	80	brown clay streaks of gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 70 to 150 ft.

Other aquifers: .....

First water at 70 feet.

Casing perforated

from 70 to 150 ft.

Size of perforations

3/16 x 12 - 4 rows

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8-5/8	+1	150	151	cement to 50'

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bail test 30 G.P.M. from 80'

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Patrick N. Thompson
Well Driller

By .....

License No. 192

Dated Oct. 16, 19 62

(Not to be filled in by Driller)