

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57169  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner G. Marquez Driller S. R. McKinney & Son

Address 526 S. Second, Las Vegas Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: NW 1/4 NW 1/4 Sec. 28, T. 20N/S, R. 62E, in Clark County

or \_\_\_\_\_

Water will be used for Domestic Total depth of well 100 ft.

Size of drilled hole 10" to 30 ft., 8" to 100 Weight of casing per linear foot 10 guage

Thickness of casing 10 guage Temp. of water \_\_\_\_\_

Diameter and length of casing 8" O.D. to 40 ft.  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 38 ft.

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well Nov 9, 1953 Date of completion of well Nov 9, 1953

Type of well rig Bucyrus Erie 24 L. Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	topsoil
8	25	17	brown clay
25	35	10	gravel dry
35	45	10	white clay
45	48	3	white sand water
48	60	12	white clay
60	65	5	white sand water
65	75	10	brown clay
75	85	10	Brown sand water
85	100	15	brown clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 75 to 85 ft.

Other aquifers 60 to 65  
45 to 48

First water at 45 feet.

Casing perforated

from none to \_\_\_\_\_ ft.

Size of perforations



