

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57222  
 Rec. 6/10 1955  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner James S. Ashley Driller Patrick H. Thompson  
 Address P. O. Box 2067 Address 217 So. 26th St LV, Nev. Lic. No. 192  
Fresno 18, California.  
 Location of well: SE 1/4 NW 1/4 Sec 20, T22-N/S, R61 E, in Clark County  
 or E1 NW1 SW1 NW1

Water will be used for Domestic Total depth of well 180'

Size of drilled hole 12" to 50' - 10" from 50 to 180' Weight of casing per linear foot 12.2

Thickness of casing 10 gauge Temp. of water cold

Diameter and length of casing 131' length 3" dia.  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 132'

If flowing well describe control works \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well June 4, 1955 Date of completion of well June 9, 1955

Type of well rig cable tool.

LOG OF FORMATIONS				Water-bearing Formation, Casing Perforations, Etc.
From feet	To feet	Thickness feet	Type of material	
0	22	22	gravel	
22	98	76	cemented gravel	
98	104	6	red clay & gravel	Chief aquifer (water-bearing formation)
104	132	28	cemented gravel	from <u>172</u> to <u>179</u> ft.
132	134	2	gravel	
134	156	22	cemented gravel	Other aquifers <u>132' - 134'</u>
156	158	2	gravel	<u>156' - 158'</u>
158	172	16	cemented gravel	
172	179	7	gravel	
179	180	1	cemented gravel	First water at <u>132</u> feet.
				Casing perforated
				from <u>130</u> to <u>180</u> ft.
				Size of perforations
				<u>2/16 x 12 -- 4 FOWS</u>

