

LVD

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57255  
 Rec. No. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
 Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner Don Van Hoy Driller S. R. McKinney & Sons Inc.

Address 1221 Ringe Lane Las Vegas Address 1042 S Main Las Vegas No. 45

Location of well: SW 1/4 NW 1/4 Sec. 28., T. 20. N/S, R. 62E, in Clark County

or \_\_\_\_\_

Water will be used for Domestic Total depth of well 200 ft.

Size of drilled hole 12" to 50 ft., 10" to 200 Weight of casing per linear foot 3/16"

Thickness of casing 3/16" Temp. of water \_\_\_\_\_

Diameter and length of casing 8 5/8 inch to 200 ft.  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 54 ft.

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 5-10-66 Date of completion of well 5-12-66

Type of well rig Bucyrus Erie 22 W Spudder

## LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	to soil
2	55	53	brown clay
55	65	10	white clay water
65	100	35	white clay
100	115	15	white sandy clay water
115	160	45	white clay
160	195	35	white sandy clay water
195	200	5	white clay

### Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 160 to 195 ft.

Other aquifers 100 to 115

55 to 65

First water at 55 feet.

Casing perforated

from 60 to 200 ft.

Size of perforations

3/16" X 10"

