

**WELL LOG AND REPORT TO THE STATE ENGINEER
OF NEVADA**

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 57275
 Rec. No. _____ 19____
 Well No. _____
 Permit No. _____
 Do not fill in.

Owner Cecil Womack Driller Patrick Thompson

Address 5019 E. Owens L.V. Address Las Vegas, Nevada Lic. No. 192

Location of well S.E. 1/4 N.W. 1/4 Sec 14, T.20 N/S, R.62 E, in Clark County
 or 1315 Bledsoe Las Vegas, Nevada

Water will be used for Domestic Total depth of well 103'

Size of drilled hole 12" to 50" 10" 50-103 Weight of casing per linear foot 12#

Thickness of casing 10 Guage Temp. of water Cool

Diameter and length of casing 8 5/8" - Diameter 104' - Length
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface..... 60'

If flowing well describe control works.....
(Type and size of valve, etc.)

Date of commencement of well 5-11-64 Date of completion of well 5-12-64

Type of well rig Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	50	50	Brown Clay
50	70	20	Brown Clay with Streaks of White Clay
70	78	8	Brown Clay
78	85	7	White Clay
85	103	18	White Clay with Streaks of Brown Clay

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 78 to 103 ft.

Other aquifers 60-78

First water at 60 feet.

Casing perforated

from 60 to 100 ft.

Size of perforations

3/16 x 12" 4 Rows

