Log No. 57276
Rec. 19
Well No. 1
Permit No. .....
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Cecil Womack Driller: Patrick H. Thompson

Address: 5019 E. Owens Las Vegas, Nev. Address: 217 So. 26 th St. Lic. No. 192

Location of well: SE 1/4 NW 1/4 Sec. 28, T. 20 N/S, R. 62 E, in Clark County

or .....

Water will be used for: Domestic Total depth of well: 100 ft.

Size of drilled hole: 0-50 ft. 12" 50-100 ft. 10" Weight of casing per linear foot: 12 lb

Thickness of casing: 10 guage Temp. of water: cool

Diameter and length of casing: 8 5/8" in Diameter 101 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface: 37 ft.

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well: Aug. 22, 1961 Date of completion of well: Aug 23, 1961

Type of well rig: Cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	15	15	Sandy soil
15	25	10	Brown sandy clay
25	45	20	White clay
45	100	55	White sandy clay and gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 45 to 100 ft.

Other aquifers .....

First water at 45 feet.

Casing perforated
from 55 to 100 ft.

Size of perforations
3/16 " X 12" 4 rows

(OVER)

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8 5/8	+ 1	100	101	Cemented to 50 ft.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bail tested 60 GPM from 47 ft.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Patrick H. Thompson
Well Driller

By.....

License No. 192

Dated September 20, 1961

(Not to be filled in by Driller)