

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. **57290**  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Rebecca Gaylinson Driller S. R. McManey & Son

Address 1241 Pearl St. Napa, California Address 1042 S. Main Las Vegas Lic. No. 45

Location of well: SE 1/4 SW 1/4 Sec 20, T. 22N/S. R. 61 E, in Clark County

or SE 1/4 of SW 1/4 of SE 1/4 of SW 1/4 of Sec. 20, Twp 22S, Range 61 East

Water will be used for Domestic Total depth of well 180 feet

Size of drilled hole 12" to 50' 10" to 180' Weight of casing per linear foot 28 lb

Thickness of casing 1/2 inch Temp. of water \_\_\_\_\_

Diameter and length of casing 8" I. D. to 181'  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 121'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well April 9, 1955 Date of completion of well 15 April, 1955

Type of well rig 24 L Bucyrus Erie Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	3	3	Sandy soil
3	120	117	Cemented gravel
120	140	20	Brown cemented gravel
140	144	4	Brown sandy clay
144	150	6	Brown cemented gravel little water
150	156	6	Brown sandy clay
156	180	24	Brown cemented gravel, water

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
156 to 180  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.

Other aquifers 144 to 150  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

First water at 144 feet.

Casing perforated  
140 to 180  
 from \_\_\_\_\_ to \_\_\_\_\_ ft.

Size of perforations  
3/16" x 10"

