

*State*  
*x*

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 57339  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner G.A. Boen Driller S.R. McKinney & Sons, Inc.

Address 4998 Monroe Address 1042 South Main Lic. No. 45

Location of well: NE 1/4 NE 1/4 Sec. 29, T. 20N/S, R. 62E, in Clark County

Water will be used for domestic Total depth of well 100 feet

Size of drilled hole 10", reamed 12" to 50 ft. Weight of casing per linear foot 10 ga.

Thickness of casing 10 ga. Temp. of water \_\_\_\_\_

Diameter and length of casing 8" to 100 feet  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 42 feet

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well 5/17/60 Date of completion of well 5/19/60

Type of well rig Bucyrus Erie 22-W, Spudder

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	25	25	gravel
25	50	25	white clay
50	70	20	white clay water
70	100	30	brown clay water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 50 to 100 ft.

Other aquifers \_\_\_\_\_

First water at 46 feet.

Casing perforated

from 60 to 100 ft.

Size of perforations

3/16" x 10"



