


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 57589
 Rec. 19
 Well No. 1
 Permit No. _____
Do not fill in

Owner Cecil Womack Driller Patrick H. Thompson
 Address Owens Ave. Sunrise Manor, Nev. Address 217 So. 26th St. L.V.N. Lic. No. 192
 Location of well: NE 1/4 NE 1/4 Sec. 29, T20 N/S, R62 E, in Clark County
 or _____
 Water will be used for Domestic Total depth of well 80'
 Size of drilled hole 10" to 50' - 8" from 50' to 80' Weight of casing per linear foot 19#
 Thickness of casing 250" Temp. of water cool
 Diameter and length of casing 6" dia. - 81' length
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure _____
 If nonflowing well give depth of standing water from surface 40'
 If flowing well describe control works _____
 (Type and size of valve, etc.) _____
 Date of commencement of well Feb. 18, 1958 Date of completion of well Feb. 20, 1958
 Type of well rig cable tools

LOG OF FORMATIONS				Water-bearing Formation, Casing Perforations, Etc.
From feet	To feet	Thickness feet	Type of material	
0	40	40	white clay	
40	42	2	sand	
42	65	23	white clay - streaks of caliche	Chief aquifer (water-bearing formation)
65	70	5	gravel	from <u>65</u> to <u>70</u> ft.
70	80	10	white clay	Other aquifers _____
				First water at <u>40</u> feet.
				Casing perforated
				from <u>55</u> to <u>80</u> ft.
				Size of perforations
				<u>3/16 x 12 - 3 rows</u>

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material
			

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"	1	80	81	Cemented to 50'

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed

Patrick H. Thompson
Well Driller

By

License No. 192

Dated March 22, 1958

(Not to be filled in by Driller)

