

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

1

Log No. 57597  
 Rec. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. 1077?  
*Do not fill in*

Owner Garn Eyre Driller Patrick H. Thompson  
 Address 4028 E. Owens, N. Las Vegas, Nev. Address 217 S. 26th St. L.V.N. Lic. No. 192  
 Location of well: NW $\frac{1}{4}$  NE $\frac{1}{4}$  Sec 30, T. 20N/S, R. 62 E, in Clark County \_\_\_\_\_

Water will be used for Domestic Total depth of well 200'

Size of drilled hole 50'-12" -- 50'-200'-10" Weight of casing per linear foot 12#

Thickness of casing 10 gauge Temp. of water cool

Diameter and length of casing 8-5/8" dia. -- 201' length  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 30'

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well May 6, 1960 Date of completion of well May 10, 1960

Type of well rig cable tools

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	7	7	sandy soil
7	30	23	white clay
30	33	3	gravel
33	44	11	white clay
44	65	21	brown sandy clay - water
65	68	3	gypsum - water
68	200	132	brown sandy clay - water

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 68 to 200 ft.

Other aquifers 65 - 68

First water at 30 feet.

Casing perforated

from 100 to 200 ft.

Size of perforations

3/16xk2 - 4 rows



